



Open Frame LCD Display kit

With Projected Capacitive touch screen (Multi-Touch)

VGA / DVI / HDMI input



Model No.	MTF104X13P	MTF121X15P	MTF150X35P	MTF170E23P	
Size(Diagonal)	10.4"	12.1"	15"	17"	
Display Format (HxV)	1024 x 768	1024 x 768	1024 x 768	1280 x 1024	Pixels
Aspect Ratio	4:3	4:3	4:3	4:3	
Brightness w/o TP	-	-	-	-	cd/m ²
Brightness (TP)	348	425	348	218	cd/m ²
Contrast Ratio	500	700	700	1000	
View Angle	75 / 75 / 60 / 80	80 / 80 / 70 / 70	80 / 80 / 70 / 70	85 / 85 / 80 / 80	
Input Signal System	HDMI/DVI/VGA	HDMI/DVI/VGA	HDMI/DVI/VGA	HDMI/DVI/VGA	
Input CVBS System	-	-	-	-	
Power Consumption (+12V)	6.6	9.6	11.4	17	Watts
Outline Dimensions (WxHxD)	265.8 x 213 x 45.7	302.4 x 234.4 x 45.6	369.69x 284.15x 47.3	402.9x 321.6x 47.2	mm
Weight	1.6	1.96	3	3.7	Kg
Operation Temperature w/o TP	-	-	-	-	°C
Operation Temperature (TP)	-20~+70	-20~+70	-20~+70	0~+50	°C
Touch Screen Panel (USB/RS232)	PCAP 2Points (USB)	PCAP 2Points (USB)	PCAP 2Points (USB)	PCAP 2Points (USB)	
Audio Amplifier	1W@8Ω/2W@4Ω	1W@8Ω/2W@4Ω	1W@8Ω/2W@4Ω	1W@8Ω/2W@4Ω	
Audio 3.5 Jack(Line-In/Out)	Line-In	Line-In	Line-In	Line-In	
Water Proof(IP54)	Option	Option	Option	Option	
Front Bezel	Yes(Full Flat Bezel)	Yes(Full Flat Bezel)	Yes(Full Flat Bezel)	Yes(Full Flat Bezel)	
Panel Mount	Option	Option	Option	Option	Hours
Material(Color)	Iron	Iron	Iron	Iron	
LED Life Time(Min.)	30K	30K	50K	50K	
Remark	-	-	-	-	