

RACK MOUNT INDUSTRIAL LCD DISPLAYS



MITSUTECH
INTERNATIONAL CORP

19" rack mount industrial metal casing with 17" LCD panel
Composite video input and optional with touch screen



Model Selection

MTK9170V 15 Pin D-Sub VGA PC graphic
With composite and S-video input

MTK9170V/Tx Optional Touch Screen
MTK9170V/TC for Capacitive
MTK9170V/TR5 for Resistive

Main Features

- ★ High Quality Image
- ★ PAL/NTSC/SECAM Video Input
- ★ User Friendly OSD
- ★ Touch Screen Option

■ Specifications

Model		MTK9170V
LCD	Screen Size	17.0" (355.6 cm) Diagonal.
	Panel Type	TFT active matrix
	Number of Pixel	1280 x 1024 (UXGA)
	Pixel Pitch	0.264 mm x 0.264mm
	Display Area (W x H)	13.30" x 10.64" (337.9x 270.3mm)
	Surface Treatment	Anti-glare and hard coat 3H ON LCD surface
	Colors	16millions
	Brightness	250 cd /m2
	Contrast	400:1(Typ.)
	Response Time	45ms
Input Signals	Video Signal	RGB Analog, 0.714 Vp-p, 75 Ω
	Synchronization	VGA-UXGA, NTSC/PAL/SECAM
	Horizontal Frequency	30 ~80 KHz,
	Vertical Frequency	50.0 ~ 85.0 Hz
Connector	Video Signal	15- pin D-SUB
	NTSC/PAL Video-in	RCA Connector x 2; S-Video connector x 1
	NTSC/PAL Video-out	RCA Connector x 1
	USB	Up stream Port x 1; Down stream x 4
Audio	Line in	Stereo (Mini Jack x 1)
	Line out	Stereo (Mini Jack x 1)
	Speaker	Stereo (3Watt x 2)
External Control	Switch	Power Switch, Choice of Input Ports,
	On-Screen Display	Brightness, Contrast, Color Control(R/G/B), Phase, Audio Control, Horizontal Size, Horizontal Position, Vertical Position, Auto Adjustment, Expansion, Recall, Reset, OSD Menu Position OSD Language (English, Japanese)
Environment	Temperature	Operating: 0 to +50 C Storage: -20 to +60 C
	Humidity	30~85%RH (Non Condensing)
Power Supply		Input AC100-240V 50/60 Hz, Output: DC 12V
Power Consumption		35W(Max.) Stand by: 4W (Max.)
Power Management		VESA DPMS
Plug & Play		DDC2B (VESA Standard)
Other Features		VESA Holes standard 75 x 75 mm
Accessories		AC Adapter & Cord, RGB Cable, Audio Cable, Video Cable, Operating Manual
Options		Touch Screen, , NTSC/PAL
Limited Warranty		One Year on Parts and Labor

Features and Specifications are subject to change without prior notice



Mitsutech International Corp.

6F, 431, Rei-Kuang Road
Taipei, Taiwan
R.O.C.
Tel: +886-2-2797-2889
Fax: +886-2-2797-1669
e-mail: info@mitsutech.com.tw
http://www.mitsutech.com.tw

Mitsutech USA Corp.

48501 Warm Springs Blvd
Suite 114
Fremont, CA94539, USA
Tel: +1-510-656-8986
Fax: +1-510-656-8167
e-mail: info@mitsutech.com
http://www.mitsutech.com

Mitsutech Asia Limited.

Room 1406, 42 Hung To Road
Kwun Tong
Kowloon, Hong Kong
Tel: +852-2304-8429
Fax: +852-2304-8217
e-mail: jimsu@lcdvision.com
Http://www.lcdvision.com