

Sharp 11.3 inch TFT LCD Module



LQ11S43

Parameter	Specifications	unit
Display size	11.3 Diagonal	inch
Active area	230.4(H)*172.8(V)	mm
Pixel format	800(H)*600(V) full dots 1pixel=R+G+B dots	pixel
Pixel pitch	0.288(H)*0.288 (V)	mm
Pixel configuration	R,G,B vertical stripe	
Contrast Ratio	150 (Min.)	
Brightness	70 (Typ.)	Cd/m ²
Response Time	80	ms
Unit outline dimensions	260.5(W)*187.0(H)*8.0Max(D)	mm
Mass	410+/-20	g
Surface treatment	Anti-glare and hard-coating 2H Low reflection (~5%)	
Storage Temp.	-25~+60	°C
Operating Temp.	0~+50	°C
Humidity	95% RH (Non-condensation)	
Power Consumption	2.25 (Typ.)	W
Backlight	1 CCFL	
Backlight life	10,000 (Min)	hr

Sharp 11.3 inch TFT LCD Module



LQ11S44

Parameter	Specifications	unit
Display size	11.3 Diagonal	inch
Active area	230.4(H)*172.8(V)	mm
Pixel format	800(H)*600(V) full dots 1pixel=R+G+B dots	pixel
Pixel pitch	0.288(H)*0.288 (V)	mm
Pixel configuration	R,G,B vertical stripe	
Contrast Ratio	150 (Min.)	
Brightness	70 (Typ.)	Cd/m ²
Response Time	80	ms
Unit outline dimensions	260.5(W)*187.0(H)*8.0Max(D)	mm
Mass	410+/-20	g
Surface treatment	Anti-glare and hard-coating 2H Low reflection (~5%)	
Storage Temp.	-25~+60	°C
Operating Temp.	0~+50	°C
Humidity	95% RH (Non-condensation)	
Power Consumption	2.25 (Typ.)	W
Backlight	1 CCFL	
Backlight life	10,000 (min)	hr